

Xerox® Phaser® 6510 Colour Printer



| System Specification | | Phaser 6510N | Phaser 6510DN |
|---|---|---|---------------|
| One-Sided Speed A4 / 210 x 297 mm | Up to 28 ppm Colour and Black and White | | |
| Two-Sided Speed A4 / 210 x 297 mm | NA | Up to 19 ppm Colour and Black and White | |
| Monthly Duty Cycle¹ | Up to 50,000 pages / month | | |
| Recommended Average Monthly Print Volume² | Up to 3,000 pages | | |
| Processor | 733 MHz | | |
| Memory | 1 GB | | |
| Connectivity | 10/100/1000Base-T Ethernet USB 3.0 | | |
| Paper Handling | | Phaser 6510N | Phaser 6510DN |
| Bypass Tray | | | |
| Capacity³ | 50 sheets | | |
| Sizes | Custom Sizes: 76 x 127 mm to 216 x 356 mm | | |
| Weights | 60 to 220 gsm | | |
| Media Types | Bond Plain Card Stock Custom Envelopes Glossy Card Stock Hole punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled | | |
| Tray 1 | | | |
| Capacity³ | 250 sheets | | |
| Sizes | Custom Sizes 76 x 147 mm to 216 x 356 mm | | |
| Weights | 60 to 176 gsm | | |
| Media Types | Bond Plain Card Stock Custom Envelopes Glossy Card Stock Hole punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled | | |
| Optional Tray 2 | | | |
| Capacity³ | 550 sheets | | |

Xerox® Phaser® 6510 Colour Printer

| Optional Tray 2 | |
|---|--|
| Sizes | Custom Sizes: 76 x 191 mm to 216 x 356 mm |
| Weights | 60 to 176 gsm |
| Media Types | Bond Plain Card Stock Custom Glossy Card Stock Hole punched Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled |
| Total Capacity | |
| Device Standard Capacity³ | 300 sheets |
| Device Total Capacity³ | 850 sheets |
| Paper Output | |
| Output Capacity³ | 150 sheets |
| Automatic 2-Sided | NA |
| | Standard |
| Device Specification | Phaser 6510N |
| | Phaser 6510DN |
| Electrical Requirements | |
| Europe | Voltage: 220-240 VAC +/- 10% Frequency: 50 Hz +/- 3 Hz, 6A |
| Power Consumption | |
| Operation⁴ | 220V: Maximum 350 watts |
| Standby Mode⁴ | 220V: Maximum 44 watts |
| Power Off Mode⁴ | 220V: Maximum 0.3 watts |
| Sleep Mode⁴ | 220V: Maximum 1.0 watts |
| Warm-up (from Sleep Mode) | As fast as 26 seconds |
| Operating Environment | |
| Required Temperature Range | |
| Storage | -20°C to 40°C |
| Operating | 5°C to 32°C |
| Required Relative Humidity | 15% to 85% |
| Sound Power Levels | |
| Operating | 6.76 B or less |
| Standby | 4.00 B or less |
| Sound Pressure Levels | |
| Operating | 51.9 dB(A) or less |
| Standby | 24.9 dB(A) or less |
| Dimensions and Weight (unpackaged) | |
| Phaser 6510N and DN | Width: 420 mm Depth: 483 mm Height: 347 mm Weight: 23.8 kg |
| 550-sheet Paper Tray | Width: 420 mm Depth: 465 mm Height: 150 mm Weight: 6.7 kg |

Xerox® Phaser® 6510 Colour Printer

| Dimensions and Weight (packaged) | | |
|--|---|---------------|
| Phaser 6510N and DN | Width: 634 mm Depth: 580 mm Height: 505 mm Weight: 29.2 kg | |
| 550-sheet Paper Tray | Width: 535 mm Depth: 584 mm Height: 248 mm Weight: 8.5 kg | |
| System Certification/Regulatory Compliance | | |
| Certifications | CE Mark applicable to Directives 2006/95/EC, 2004/108/EC and 1999/5/EC GS Mark Citrix™ Certified Cerner (undergoing evaluation) Apple® AirPrint® certification Google Cloud Print™ Certification Mopria® certified Wi-Fi Alliance Certified Blue Angel MEDITECH ENERGY STAR® To view the latest list of certifications, go to www.xerox.com/OfficeCertifications . | |
| Print | Phaser 6510N | Phaser 6510DN |
| First-Page-Out Time | As fast as 12 seconds Colour and Black and White | |
| Resolution | Up to 1200 x 2400 dpi | |
| Page Description Languages | Adobe® PostScript® 3™ PCL® 5e, 6 PDF TIFF | |
| Maximum Print Area | 4 mm from all edges | |
| Print Features | Banner Sheets Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Poster Printing Proof Print RAM Collation Run Black Saved Print Secure Print Watermarks | |
| Print from USB | Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS | |
| Operating Systems | Windows®, 7, 8, 10, Server 2000, Server 2003, Server 2008, Server 2008 R2, Server 2012 Mac OS® version 10.5 and higher Citrix® Redhat® Enterprise Linux® IBM® AIX® 5 HP-UX® 11iv2 Oracle® Solaris 9, 10 Fedora Core 12-15 SUSE® | |

Xerox® Phaser® 6510 Colour Printer

| Print | Phaser 6510N | Phaser 6510DN |
|---|---|----------------------|
| Network Protocols | TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD SMB SMTP, Secure SMTP LDAP, Secure LDAP Bonjour® / Airprint® FTP Most protocols not in use can be disabled | |
| Administrative Protocols | DHCP, SNMP v2/3, WINS, DHCP Autonet, TLS, SNMP, MDNS | |
| Font Capability | 136 PostScript fonts 88 PCL fonts | |
| Mobile Solutions and Mobile Device Apps | | |
| Xerox® Mobile Express Driver® | Makes it easy for mobile users to find, use and manage Xerox® and non Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT. | |
| Xerox® Global Print Driver® | A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management. | |
| Apple® AirPrint® | Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network. | |
| Google Cloud Print™ | Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device. | |
| Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store) | The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store. | |
| Xerox® Wireless Print Solutions Adapter (Optional) | The Xerox® Wireless Print Solutions Adapter seamlessly connects your Xerox® printer or MFP to modern mobile and desktop workflows, regardless of your office environment. For more information, visit www.xerox.com/WPSA | |
| Security | Phaser 6510N | Phaser 6510DN |
| Security Features | Secure HTTPS (TLS) IPsec 802.1x Authentication S/MIME IP Filtering Secure Print SNMP v3 LDAP (SASL) | |
| Device Management | | |
| Xerox® CentreWare® Web | | |
| | <ul style="list-style-type: none"> • A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. | |
| Xerox® Embedded Web Server - Integrated Device Web Page | | |
| Device Status | Web server embedded <ul style="list-style-type: none"> • Tray status/contents • Consumables status | |
| Print Queue Viewing | Complete job print queue management—hold, release, promote and delete | |
| Job Submission | Print-ready files (PS, PCL®, PDF, XPS, JPEG) Output feature selection | |
| Device Administration | Allows simple, remote installation setting of configuration options and management of the device. | |
| Browsers | Microsoft® Internet Explorer 11 Microsoft Edge™ 38 Mozilla™ Firefox® 48 Apple® Safari® 9.1 Google Chrome™ 52 Opera™ 39 | |
| Remote Print Services | | |
| Automated Meter Reading (AMR) | Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time. | |

Xerox® Phaser® 6510 Colour Printer

| Remote Print Services | | |
|---|--|--|
| Automated Supplies Replenishment (ASR) | Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory. | |
| What's In The Box | | |
| | <ul style="list-style-type: none"> • Phaser 6510 Colour Printer • Standard Capacity Print cartridge: One of each (Cyan, Magenta, Yellow: 1,000 print capacity⁵; Black: 1,500 print capacity⁵) • Software and Documentation CD (with User Manual, Quick Install Guide, Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) • Installation Guide • Quick Use Guides • Power cord | |
| Supplies and Accessories | Quantity | Part Number |
| Supplies | | |
| Extra-High Capacity Print Cartridges | Cyan: 4,300 standard pages ⁵ Magenta: 4,300 standard pages ⁵ Yellow: 4,300 standard pages ⁵ | 106R03690 106R03691 106R03692 |
| High Capacity Print Cartridges | Black: 5,500 standard pages ⁵ Cyan: 2,400 standard pages ⁵ Magenta: 2,400 standard pages ⁵ Yellow: 2,400 standard pages ⁵ | 106R03480 106R03477 106R03478 106R03479 |
| Standard Capacity Print Cartridges | Black: 2,500 standard pages ⁵ Cyan: 1,000 standard pages ⁵ Magenta: 1,000 standard pages ⁵ Yellow: 1,000 standard pages ⁵ | 106R03476 106R03473 106R03474 106R03475 |
| Drum Cartridge | Black: 48,000 pages ⁶ Cyan: 48,000 pages ⁶ Magenta: 48,000 pages ⁶ Yellow: 48,000 pages ⁶ | 108R01420 108R01417 108R01418 108R01419 |
| Waste Cartridge | 30,000 pages ⁵ | 108R01416 |
| Accessories | | |
| 550-sheet Paper Tray | | 097S04765 |
| Wireless Network Adapter | | 497K16750 |

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

² Expected regular monthly throughput.

³ Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

⁴ Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.

⁵ Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode.

⁶ Approximate pages. Declared Yield based on A4-size 75 gsm pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.

Xerox® Phaser® 6510 Colour Printer

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme.
For more information, visit www.xerox.com/about-xerox/recycling.

For more information, visit us at www.xerox.com/office



©2016 Xerox Corporation. All rights reserved. Xerox®, Xerox and Design®, CentreWare®, Global Print Driver®, Mobile Express Driver®, and Phaser® are trademarks of Xerox Corporation in the United States and/or other countries. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency (DN configuration). ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. The information in this brochure is subject to change without notice.

11/16 BR19948 65XSS-01EA